## LOC PORCELANOSA Grupo

## Declaration of Performance



## No 20130701CPR016

The undersigned RÉMI SCANO, as legal representative of the company L'ANTIC COLONIAL S.A. based in carretera 340, km 55.8, 12540 Villarreal (Castellón) Spain, phone (+34) 964 53 45 45, fax (+ 34) 964 52 42 58, e-mail: anticcolonial@anticcolonial.com

Declares

Under his sole responsibility declares that the company L'ANTIC COLONIAL provides the EC classification in accordance with appendix III of (EU) Regulation No. 305/2011 (construction products regulations):

Agglomerated stone. Modular tiles for flooring (indoor and outdoor use) UNE-EN 15285:2009

An assessment and verification system is established to determine the existence of performances, in this case being those of System 3 DQS Agglomerated Stone

Characteristics	Standard	Units	Value / Category
Water absorption	UNE-EN 14617:2013	-	W4 Class
Flexural strength		-	F3 Class
Resistance to abrasion		-	A4 Class
Chemical resistance		-	C4
Resistance to thermal shock		%	$\Delta m$ = -0.08
Tactile quality/Visibility		-	NDP
Coefficient of linear thermal expansion		1/ºC	=19 - 26.10-6
Electrical resistivity		$\Omega$ m $\Omega$	Pp volume > 4.10 <sup>11</sup> p surface > 4.10 <sup>11</sup>
Resistance to shock		Joules	2
Dimensional stability		-	Class A
Flammability	UNE-13501-1:2009	-	A2a-s1
Thermal conductivity	UNE-EN 12524:2001	W/(m.K)	1.28
Slippage	UNE EN 14231:2004	$\begin{array}{l} Rd \leq 15 \; (Class \; 0), \; 15 < \\ Rd \leq 35 \; (Class \; 1), \; 35 < \\ Rd \leq 45 (Class \; 2), \; and \\ Rd > 45 \; (Class \; 3) \end{array}$	Dry (Class 2) / Wet (Class 1)

This declaration of performance is issued and signed on behalf of the company.

Signature:

Place and date of issue:

On July 2, 2018, Villareal (Castellón) - Spain

Mr. Rémi Scano Manager