

Declaration of Performance



No 20130701CPR007

The undersigned RÉMI SCANO, as legal representative of the company L'ANTIC COLONIAL S.A. based in carretera 340, km 55.8, 12540 Villarreal (Castellón) Spain, phone (+34) 964 53 45 45, fax (+34) 964 52 42 58, e-mail: anticcolonial@anticcolonial.com

Declares

Under his sole responsibility declares that the company L'ANTIC COLONIAL provides the EC classification in accordance with appendix III of (EU) Regulation No. 305/2011 (construction products regulations):

Finishings for indoor and outdoor floors, stairs, and walls, for persons and vehicles, subject to the current legislation regarding flammability UNE - EN 12058, UNE EN 1469, and UNE EN 1341

An assessment and verification system is established to determine the existence of performances, in this case being those of System 4

Sandstone Tiles

Characteristics	Standard	Units	Value / Category
Emission of hazardous substances	UNE-EN 12058, UNE EN 1469, and UNE EN 1341	-	-
Petrographic description		-	Sandstone
Bulk density and open porosity		Kg/m ³ // %	> 2460 / 0.17
Absorption at atmospheric pressure		%	> 4.3 %
Water absorption by capillarity		g/m ² .s ^{0.5}	23.0
Flammability		-	A1/A1fl
Slip resistance		Rd ≤ 15 (Class 0), 15 < Rd ≤ 35 (Class 1), 35 < Rd ≤ 45(Class 2), and Rd > 45 (Class 3)	Dry (Class 2) / Wet (Class 1) *Sand home and lined home finishings: Dry (Class 3) / Wet (Class 2)
Skid resistance		-	NDP
Tactile quality/Visibility		-	NDP
Thermal conductivity		W/(m.K)	1.3
Flexural strength		MPa	> 7.2
Frost resistance		MPa	> 5.6
Resistance to thermal shock		%	Δmass=0.01 / Flexural modulus =12.30
Resistance to abrasion		mm	> 24.0
Water vapor permeability		μ	250 / 200
Resistance to anchoring		Newtons	On request for fasteners with bolt anchor

This declaration of performance is issued and signed on behalf of the company.

Signature:

Mr. Rémi Scano
Manager

Place and date of issue:

On July 2, 2018, Villarreal (Castellón) - Spain