

Declaration of Performance



No 20130701CPR002

The undersigned RÉMI SCANO, as legal representative for the company L'ANTIC COLONIAL, S.A. located in Carretera N.340 Km. 55,8 12540 Villareal (Castellón) Spain, phone (+34) 964 53 45 45, fax (+34) 964 52 42 58, e-mail: anticcolonial@anticcolonial.com

Declares

Under his sole responsibility declares that the company L'ANTIC COLONIAL provides the EC classification in accordance with appendix III of (EU) Regulation No. 305/2011 (construction products regulations):

Finishings for indoor and outdoor floors, stairs, and walls, for persons and vehicles, subject to the current legislation regarding flammability UNE - EN 12058, UNE EN 1469, and UNE EN 1341

An assessment and verification system is established to determine the existence of performances, in this case being those of System 4

Travertine Tiles

Characteristics	Standard	Units	Value / Category
Emission of hazardous substances	UNE-EN 12058, UNE EN 1469, and UNE EN 1341	-	-
Petrographic description		-	Travertine
Bulk density and open porosity		Kg/m <sup>3</sup> // %	> 2400 // 8.00
Absorption at atmospheric pressure		%	1.5 - 4
Water absorption by capillarity		g/m <sup>2</sup> .s <sup>0.5</sup>	23.2
Flammability		-	A1/A1fl
Slip resistance		Rd ≤ 15 (Class 0), 15 < Rd ≤ 35 (Class 1), 35 < Rd ≤ 45(Class 2), and Rd > 45 (Class 3)	Dry (Class 2) / Wet (Class 1) *Sand home and lined home finishings: Dry (Class 3) / Wet (Class 2)
Skid resistance		-	NDP
Tactile quality/Visibility		-	NDP
Thermal conductivity		W/m.K	2.5
Flexural strength		MPa	> 9.0
Frost resistance		MPa	> 7.6
Resistance to thermal shock		%	Δmass=0.03 / Flexural modulus =3.50
Resistance to abrasion		mm	> 22.5
Water vapor permeability		μ	200 / 150
Resistance to anchoring		Newtons	On request for fasteners with bolt anchor

This declaration of performance is issued and signed on behalf of the company.

Signature:

Mr. Rémi Scano  
Manager

Place and date of issue:

On July 2, 2018, Villareal (Castellón) - Spain